



CURVE SENZA SALDATURA 90°
RAGGIO= 1,5 D DIMA 3

ASME B16.9 ASTM A 403
 WP 304/304L E WP 316/316L

D.E. POLLICI	Ø EST. MM X SPESS. MM	SCH	CURVE	PESO KG/PZ.
			90° A	
1/2"	21.34 x 2.11	10S	38	0.06
	21.34 x 2.77	40S		0.08
	21.34 x 3.73	80S		0.10
	21.34 x 4.78	160		0.15
3/4"	26.67 x 2.11	10S	38	0.07
	26.67 x 2.87	40S		0.09
	26.67 x 3.91	80S		0.11
	26.67 x 5.56	160		0.23
1"	33.40 x 2.77	10S	38	0.14
	33.40 x 3.38	40S		0.16
	33.40 x 4.55	80S		0.22
	33.40 x 6.35	160		0.25
1 1/4"	42.16 x 2.77	10S	48	0.23
	42.16 x 3.56	40S		0.25
	42.16 x 4.85	80S		0.40
	42.16 x 6.35	160		0.42
1 1/2"	48.26 x 2.77	10S	57	0.30
	48.26 x 3.68	40S		0.40
	48.26 x 5.08	80S		0.51
	48.26 x 7.14	160		0.65
2"	60.33 x 2.77	10S	76	0.51
	60.33 x 3.91	40S		0.71
	60.33 x 5.54	80S		0.91
	60.33 x 8.71	160		1.33
2 1/2"	73.03 x 3.05	10S	95	0.85
	73.03 x 5.16	40S		1.36
	73.03 x 7.01	80S		1.81
	73.03 x 9.53	160		2.33
3"	88.90 x 3.05	10S	114	1.22
	88.90 x 5.49	40S		2.18

D.E. POLLICI	Ø EST. MM X SPESS. MM	SCH	CURVE	PESO KG/PZ.
			90° A	
3"	88.90 x 7.62	80S	114	2.98
	88.90 x 11.13	160		3.83
4"	114.30 x 3.05	10S	152	2.15
	114.30 x 6.02	40S		4.17
	114.30 x 8.56	80S		6.18
	114.30 x 13.49	160		8.02
5"	141.30 x 3.40	10S	190	3.63
	141.30 x 6.55	40S		6.86
	141.30 x 9.53	80S		9.58
6"	168.28 x 3.40	10S	229	4.90
	168.28 x 7.11	40S		10.90
	168.28 x 10.97	80S		16.33
8"	219.08 x 3.76	10S	305	10.66
	219.08 x 8.18	40S		21.50
	219.08 x 12.70	80S		33.11
10"	273.05 x 4.19	10S	381	19.50
	273.05 x 9.27	40S		38.60
12"	323.85 x 4.57	10S	457	27.22
	323.85 x 9.53	40S		59.40
14"	355.60 x 4.78	10S	533	36.30
	355.60 x 9.53	40S		70.30
16"	406.40 x 4.78	10S	610	47.63
	406.40 x 9.53	40S		91.60
18"	457.20 x 4.78	10S	686	59.87
	457.20 x 9.53	40S		113.00
20"	508.00 x 5.54	10S	762	99.79
	508.00 x 9.52	40S		140.00
24"	609.60 x 6.35	10S	914	140.61
	609.60 x 9.52	40S		207.80

Nota: i dati tecnici su questo catalogo sono indicativi e non impegnativi